

DECLARATION OF PERFORMANCE

Reference number **DOP07REV3 MEDITE EXTERIOR MDF.H-2**

MEDITE
Redmondstown
Clonmel,
County Tipperary,
Ireland


Product type	Intended use	AVCP*	Notified Body reference
MDF.H-2	External use as non-structural components	4	Not Applicable
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

Declared Performance

Essential characteristics	Performance						Harmonised technical specification
	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	
Thickness Range							EN 13986:2004+A1:2015
Internal bond (N/mm ²)	0.70	0.70	0.80	0.80	0.75	0.75	
Moisture Resistance Internal bond after boil test (N/mm ²)	0.20	0.20	0.15	0.15	0.12	0.12	
Thickness Swelling (24hrs) %	30	18	12	10	8	7	
Release of formaldehyde	E1	E1	E1	E1	E1	E1	
Reaction to fire	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0	
Water vapour permeability μ	NPD	NPD	NPD	NPD	NPD	NPD	
Airborne sound insulation (surface mass) (R)	NPD	NPD	NPD	NPD	NPD	NPD	
Thermal conductivity	NPD	NPD	NPD	NPD	NPD	NPD	
Biological durability	Use Classes 1,2 & 3						
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	

The performance of the product identified is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Tom Prendergast, Technical Manager.

Clonmel, Ireland. 03rd October 2016.