



Document	KR/MSDS/0001
Created by: D.Kalnunde	DATE 13.02.2019
Approved by: D.Kalnunde	Printed:
Version: 3.0	Page 1 of 3

## Material Safety Data Sheet

### 1. Identification of the Substance, Preparation and Company

*Product Name/Type:*

Chipboard P2 (Superfine)  
Chipboard P3 (Moisture Resistant Superfine)  
Chipboard P4 (Flooring)  
Chipboard P5 (Moisture Resistant Flooring)  
Chipboard P6 (Fast Floor, Flooring)  
Melamine-faced Chipboard (MFC)  
Oriented Strand Board (OSB)

*Application:*

Building, furniture, decorative fixtures and fittings

*Supplier:*

SIA "KRONOSPAN Riga"  
Daugavgrivas soseja 7B,  
Riga  
LV-1016  
Latvia  
+371 67 43 68 35

*Contact:*

### 2. Hazards Identification

*Physical Hazard:*

Not classified

*Health Hazard:*

Respiratory sensitizer

### 3. Composition/Information on Ingredients

No materials identified for this purpose as specified in The CLP Regulations (Classification, Labelling and Packaging) 2008.

Wood panel products contain the following:

Wood (various species of softwood): 77 – 91.6 %

Polymerised Resin (UF, MUF, Phenolic, p-MDI): 8 – 20 %

Wax and Hardener: 0.4 – 3.0 %

### 4. First Aid Measures

*Inhalation:*

Inhalation of wood dust can only occur during processing. If inhalation of dust causes adverse effects, remove to fresh air. If discomfort persists seek medical advice.

*Skin Contact:*

In case of irritation from dust generated when processing product, wash with water.



Document	KR/MSDS/0001
Created by: D.Kalnunde	DATE 13.02.2019
Approved by: D.Kalnunde	Printed:
Version: 3.0	Page 2 of 3

*Eyes:*

If particles enter the eyes during processing immediately flush eyes with plenty of water. Seek medical attention if irritation persists.

## 5. Fire Fighting Measures

Not flammable at room temperature but will burn. In case of fire, soak or flood with water. For large fires, fire fighters should wear appropriate emergency protective equipment, including self-contained breathing apparatus. Airborne wood dust may present an explosion hazard; standard precautions for dust control should be followed.

## 6. Accidental Release Measures

The product does not represent a hazard in sheet form. However, wood dust generated during processing should be contained, collected and removed.

## 7. Handling and Storage

### *Manual Handling*

In sheet form the product can present a manual handling risk due to physical dimensions and weight. Good lifting practice should be followed.

### *Storage*

Keep away from heat, sparks, flames and other ignition sources. Store at room temperature. Keep away from moisture. Take care when removing packaging.

## 8. Exposure Controls/Personal Protection

*Exposure Controls* – During processing, the primary control for airborne dust is extract ventilation at source. Areas where processing is taking place should also be well ventilated.

*Eyes* – Wear safety glasses with side shields.

*Respiratory* – In case of dust emanation, wear a dust mask or cartridge mask for fine particle.

*Hands* – Work gloves in order to prevent cuts, splinters and abrasions.

*Skin* – Standard work clothing.

*Work and Hygiene practices* – Follow good hygienic and housekeeping practices. Clean up areas where dust settles to avoid excessive accumulation of this combustible material. Minimize blow down or other practices that generate high airborne dust concentrations.

## 9. Physical and Chemical Properties

*Appearance:*

Wood-panels in various dimensions.

*Odour:*

None under ambient conditions.

## 10. Stability and Reactivity

Considered stable and inert.

*Materials to avoid:*

Reducing and oxidizing agents.



Document	KR/MSDS/0001
Created by: D.Kalnunde	DATE 13.02.2019
Approved by: D.Kalnunde	Printed:
Version: 3.0	Page 3 of 3

*Conditions to avoid:*

Heating and ignition sources and damp atmospheres.

*Thermal decomposition products may include:*

CO, CO<sub>2</sub>, aldehydes (including formaldehyde), particulate matter and other organic compounds.

## 11. Toxicological Information

Wood-panels are composed of softwood of various species bound together with a urea-formaldehyde resin. When it is machined, very fine dust is produced. As with other types of softwood dust, wood-panel dust is a potentially hazardous substance and should therefore be controlled. Softwood dust is not classified as a carcinogen.

## 12. Ecological Information

*Mobility:* Not determined

*Degradability:* Not determined

*Bioaccumulative Potential:* Not determined

*Aquatic Toxicity:* Not determined

## 13. Disposal Considerations

Manufacturing waste must be disposed of as Controlled Waste. The raw product is not classified as Hazardous Waste. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## 14. Transport Considerations

*Road (ADR):* Not dangerous

*Railway (RID):* Not dangerous

*Sea (IMDG):* Not dangerous

*Air(ICAO/IATA):* Not dangerous

## 15. Regulatory Information

None

## 16. Other Information

The above data has been presented in form of a Material Safety Data Sheet for information only. The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. Kronospan makes no warranty of any kind, expressed or implied, concerning the accuracy or completeness of the information and data herein.