



CONFORMITY TO ISMP 15 STANDARD

16/05/2014

FOR PLYWOOD BEING USED AS WOOD PACKAGING MATERIAL
IN INTERNATIONAL TRADE

English / Anglais

As the below stated attestation clearly mentions by referring to the ISMP 15 regulation, plywood products do not need to be specifically treated and to be marked. Only solid timber has to be treated and marked accordingly.

ISMP 15 REGULATION

The THEBAULT Group of companies certifies that plywood products such as listed in the table below are manufactured from veneers dried at a temperature of 200°C and hot pressed at a temperature comprised between 120° C and 145° C.

As a matter of consequence they fulfil the requirements of the ISMP 15 regulation:
Publication N° 15, Version 2002, Chapter N° 2/ Paragraph N° 2 as they are considered as:

"Having been sufficiently processed to have eliminated the risk associated with the raw wood"

OKOUME PLYWOOD JEAN THEBAULT SAS F - 79460 -MAGNE	MARITIME PINE PLYWOOD SIB THEBAULT SAS F - 79190 SAUZE - VAUSSAIS THEBAULT PLY - LAND SAS F - 40210 SOLFERINO
TEBOPLY OKOUME INT™ TEBOPLY OKOUME EXT™ TEBOPLY BI- TWIN OKOUME EXT™ TEBOMARINE OKOUME EXT™ TEBOLUX MARINE OKOUME EXT™ TEBOGARANT OKOUME EXT™ TEBOFLAM OKOUME INT™ TEBOFLAM OKOUME™ TEBOPROFIL OKOUME EXT™ TEBOPAINT OKOUME EXT™ TEBOPRIME OKOUME EXT™ TEBOPOLAR PEUPLIER™ TEBOPOLAR PRIME PEUPLIER™	TEBOPIN CLEAR™ TEBOPIN STAR™ TEBOPIN ELITE™ TEBOPIN SELECT™ TEBOPIN EUROPANEL™ TEBOPIN STANDARD™ TEBOFLOOR™ II / III TG2 & 4 TEBOPIN SOLID™ TEBOPIN III™ TEBOPIN ROOF™ II / III TG2 & 4 TEBOPIN PROFIL™ TEBOPIN PROFIL™ TEBOPIN FILM™ Film / Film

Jean - Charles THEBAULT
President